

MSDS-VOGAFLOOR 152

PAGE 1/8

VOGEL SYSTEMS Safety data sheet

Date / Revised: 19.09.2022 Version: 1.0

Product: MSDS-VOGAFLOOR 152

Date of print 20.09.2022

1.Identification

Product identifier VOGAFLOOR 152

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Product for construction chemicals Recommended use: for industrial and professional users







Details of the supplier of the safety data sheet

E-mail address: info@vogel-systems.de

Emergency telephone number

International emergency number

Date / Revised: 19.09.2022 Version: 1.0

Product: MSDS- VOGAFLOOR 152

Date of print 20.09.2022

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name VOGAFLOOR 152

2. Relevant identified uses of the substance or mixture and uses advised against

<u>Identified uses</u>: Solvent-free epoxy coating for concrete floors

3. Details of the supplier of the safety data sheet

<u>Supplier</u>

Company name: Vogel co.

E-mail address: info@vogel-systems.de

2. COMPOSITION/INFORMATION ON INGREDIENTS

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317

Most important adverse effects: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS07: Exclamation mark

GHS09: Environmental





Signal words: Warning

Precautionary statements: P280: Wear protective gloves/protective clothing/eye protection/face protection.

P273: Avoid release to the environment.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

Date / Revised: 19.09.2022 Version: 1.0

Product: MSDS- VOGAFLOOR 152

Date of print 20.09.2022

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water.

P391: Collect spillage.

P501: Dispose of contents/container to licensed, permitted incinerator, or other thermal

destruction device.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

3. COMPOSITION

3.1. Mixtures

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT} - REACH registered number(s): 01-2119456619-26

EINECS	CAS	PBT / WEL	CLP Classification	Percent
500-033-5	25068-38-6	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	50-70%

OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES - REACH registered number(s): 01-2119485289--22

271-846-8	68609-97-2	-	Skin Irrit. 2: H315; Skin Sens. 1: H317	10-30%	

BISPHENOL F EPICHLOROHYDRIN RESIN WITH NUMBER AVERAGE - REACH registered number(s): 01-2119454392-40

500-006-8	9003-36-5	-	Skin Irrit. 2: H315; Skin Sens. 1: H317;	10-30%
			Aquatic Chronic 2: H411; Eye Irrit. 2:	
			H319	

4. FIRST AID MEASURES

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Date / Revised: 19.09.2022 Version: 1.0

Product: MSDS- VOGAFLOOR 152

Date of print 20.09.2022

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

5. FIRE FIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the

storage room must be impermeable to prevent the escape of liquids.

Date / Revised: 19.09.2022 Version: 1.0

Product: MSDS- VOGAFLOOR 152

Date of print 20.09.2022

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be

impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves. Breakthrough time of the glove material > 8 hours. Material of gloves

for long term application(BTT>480min) Nitrile gloves. Butyl gloves. Neoprene gloves. PVC gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material and dexterity. Always seek advice from glove suppliers. Use gloves approved to relevant standards e.g. EN 374

(Europe), F739 (US)

Eye protection: Safety glasses. Ensure eye bath is to hand. Goggles giving complete protection to eyes

and eyewash bottle with clean water.

Skin protection: Protective clothing.

Environmental: Ensure emissions from ventilation or equipment comply with environmental protection

legislation.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow

Odour: Barely perceptible odour

Viscosity: Viscous

Boiling point/range°C: >100 Flash point°C: >100

Relative density: 1.12 pH: Not applicable.

9.2. Other information

Other information: No data available.

Version: 1.0

VOGEL SYSTEMS Safety data sheet

Date / Revised: 19.09.2022

Product: MSDS- VOGAFLOOR 152

Date of print 20.09.2022

10. STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
ORL	-	LD50	>2000	mg/kg
SKN	-	LD50	>2000	mg/kg

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES

ORL	RAT	LD50	17100	mg/kg	
				J J	

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Date / Revised: 19.09.2022 Version: 1.0

Product: MSDS- VOGAFLOOR 152

Date of print 20.09.2022

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

12. ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Date / Revised: 19.09.2022 Version: 1.0

Product: MSDS- VOGAFLOOR 152

Date of print 20.09.2022

14. TRANSPORT INFORMATION

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

16. OTHER INFORMATION

Phrases used in s.2 and s.3: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.