

VOGA HI-LACK

PAGE 1 / 3

VOGEL SYSTEMS Technical data sheet
Date / Revised: 19.09.2018
Product: **VOGA HI-LACK**

Version: 1.0

Date of print 20.09.2018

1. Identification

Product identifier

VOGA HI-LACK

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Product for construction chemicals
Recommended use: for industrial and professional users



Details of the supplier of the safety data sheet

Company:
VOGEL SYSTEMS
Operating Division Construction Chemicals

E-mail address: info@vogel-systems.de

Emergency telephone number

International emergency number

High Quality Synthetic Enamel - Gloss

DESCRIPTION

VOGA HI-LACK is a high-quality gloss enamel paint based on modified alkyd resins to provide an excellent gloss smooth finish.

APPLICATION FIELDS

VOGA HI-LACK compatible with all surface materials such as block, concrete , plaster , rendered walls ..etc , for exterior and interior usage.

ADVANTAGES

- High Gloss
- Excellent hiding power.
- High-quality finishes
- Easy to Use

APPLICATION INSTRUCTIONS

VOGA HI-LACK must be applied to a clean , dry substrate free from laitance , dust , dirt , oil , grease and other contaminants.

APPLICATION

- Remove dirt, surface dust, laitance and any surface contamination e.g.
- Use **VOGASEAL-LACK** as a sealer to improve adhesion rate.
- Use white spirit (up to 25%) to dilute the product depending on method of application .
- Mix **VOGA HI-LACK** well then apply 2 coats in D.F.T 30~40 µm/coat.

TECHNICAL DATA

Product properties at 25°C	
Finish	Gloss
colour	White and standard colours
Density	1.2 kg/Lt
Solid content by volume	51±2%
DILUENTS / THINNER	White spirit / thinner
DRYING TIME	Recoat: 2-4 hours / Full Dry : 1 day.

VOGEL SYSTEMS Technical data sheet

Date / Revised: 19.09.2018

Product: **VOGA HI-LACK**

Version: 1.0

Date of print 20.09.2018

APPLICATION TOOLS

Apply **VOGA HI-LACK** with brush – roller – spray gun .

CONSUMPTION

Estimated consumption for **VOGA HI-LACK** is 13-17 m²/ltr .

PACKAGING

VOGA HI-LACK is supplied in 5 , 15 , 25 kg pail.

CLEANING

Tools and equipment should be cleaned, immediately after use, with thinner .
Once product cures, this can only be removed by mechanical means.

SAFETY AND HEALTH

VOGA HI-LACK is a low toxicity product but direct contact with skin and eyes must be avoided . Use rubber gloves and safety goggles when handling, mixing and applying the product .

STORAGE

Twenty four months in its unopened original packaging. Store in a cool, dry and covered place, protected from moisture , frost and direct sunlight, with temperatures between 5 °C and 30 °C.