

VOGA LACK

PAGE 1 / 3

VOGEL SYSTEMS Technical data sheet
Date / Revised: 19.09.2018
Product: **VOGA LACK**

Version: 1.0

Date of print 20.09.2018

1. Identification

Product identifier

VOGA LACK

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Product for construction chemicals
Recommended use: for industrial and professional users



Details of the supplier of the safety data sheet

Company:
VOGEL SYSTEMS
Operating Division Construction Chemicals

E-mail address: info@vogel-systems.de

Emergency telephone number

International emergency number

Super Quality Synthetic Enamel-Matt

DESCRIPTION

VOGA LACK is a fast drying superior matt enamel formulated with high quality alkyd resins and selected additives that provides it with special characteristics.

APPLICATION FIELDS

VOGA LACK compatible with all surface materials such as block, concrete , plaster , rendered walls ..etc , for exterior and interior usage.

ADVANTAGES

- Matt finish
- Good hiding power
- High-quality smooth finish
- Fast dry
- Bright white
- High durability & Easy to sand

APPLICATION INSTRUCTIONS

VOGA LACK must be applied to a clean , dry substrate free from laitance , dust , dirt , oil , grease and other contaminants.

APPLICATION

- Remove dirt, surface dust, laitance and any surface contamination e.g.
- Use **VOGASEAL-LACK** as a sealer to improve adhesion rate.
- Use white spirit (up to 25%) to dilute the product depending on method of application .
- Mix **VOGA LACK** well then apply 2 coats in D.F.T 30~40 µm/coat.

TECHNICAL DATA

Product properties at 25°C	
Finish	matt
colour	White and standard colours
Density	1.62 kg/Lt
Solid content by volume	51 ± 2%
DILUENTS / THINNER	White spirit / thinner
DRYING TIME	Recoat: 2-4 hours / Full Dry : 14 hours

VOGEL SYSTEMS Technical data sheet

Date / Revised: 19.09.2018

Product: **VOGA LACK**

Version: 1.0

Date of print 20.09.2018

APPLICATION TOOLS

Apply **VOGA LACK** with brush - roller - spray gun .

CONSUMPTION

Estimated consumption for **VOGA LACK** is 13-15m²/ltr .

PACKAGING

VOGA LACK is supplied in 5 , 15 , 25 kg pail.

CLEANING

Tools and equipment should be cleaned, immediately after use, with thinner .
Once product cures, this can only be removed by mechanical means.

SAFETYAND HEALTH

VOGA LACK is a low toxicity product but direct contact with skin and eyes must be avoided . Use rubber gloves and safety goggles when handling, mixing and applying the product .

STORAGE

Twenty four months in its unopened original packaging. Store in a cool, dry and covered place, protected from moisture , frost and direct sunlight,with temperatures between5 °C and 30 °C.