

VOGA PRO-P

PAGE 1 / 3

VOGEL SYSTEMS Technical data sheet
Date / Revised: 19.09.2018
Product: **VOGA PRO-P**

Version: 1.0

Date of print 20.09.2018

1. Identification

Product identifier

VOGA PRO-P

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Product for construction chemicals
Recommended use: for industrial and professional users



Details of the supplier of the safety data sheet

Company:
VOGEL SYSTEMS
Operating Division Construction Chemicals

E-mail address: info@vogel-systems.de

Emergency telephone number

International emergency number

Acrylic Sand ,Cement leveling & Repairing Binder

DESCRIPTION

VOGA PRO-P 100% acrylic emulsion liquid binder & sand cement powder designed for on-site leveling and repairing cracks and low spots and depression up to 20mm deep and 25 mm width . On sport acrylic / EPDM surfaces.

WHERE TO USE

1. Tennis courts .
2. Multi purpose courts .
3. Concrete & Asphalt

APPLICATION

- Surface Preparation:
 - Surfaces must be clean from dust , dirt ,debris and loose material.
 - New concrete or asphalt must cure 28 days.

ADVANTAGES

- | | |
|--|---|
| <ol style="list-style-type: none">1. Ideal for leveling & repairing.2. Easy to use.3. Safe & Eco – friendly.4. Weather & UV – resistance. | <ul style="list-style-type: none">• Mixing:<ul style="list-style-type: none">- Power or hand mix Part A & B thoroughly until a uniform creamy consistency is obtained for (2-4 minutes).- If the mix appears too dry , add water. |
|--|---|

CONSUMPTION

- | | |
|---|--|
| <ul style="list-style-type: none">• 1 kg /m2 / 1mm thickness. | <ul style="list-style-type: none">• Application:<ul style="list-style-type: none">- Apply with smooth trowel or a squeegee for leveling. |
|---|--|

PACKAGING

- | | |
|--|--|
| <p>(A+B) 5,20 kg sacks & Pails .</p> | <ul style="list-style-type: none">- Apply in multiple lifts to achieve desired depth in patches greater than 25 mm.- Allow surfaces to cure for 24 hours. |
|--|--|

TECHNICAL DATA

Product properties	
Base	Acrylic emulsion
Color	Milky White
Density	1.2 ± 0.2 gm/cm ³
Flash point	None

CLEANING

Tools and equipment should be cleaned, immediately after use, with water .
Once product cures, this can only be removed by mechanical means.

STORAGE

Twelve months in its unopened original packaging. Store in a cool, dry and covered place, protected from moisture , frost and direct sunlight , with temperatures between 5 °C and 30 °C.

SAFETY AND HEALTH

VOGA PRO-P is :

- a non-toxic product but direct contact with skin and eyes must be avoided .
- Use rubber gloves and safety goggles when handling, mixing and applying the product.
- Working areas should be well ventilated.