

VOGAEVA 200AS

PAGE 1/3

VOGEL SYSTEMS Technical data sheet Date / Revised: 19.09.2018 Product: **VOGAEVA 200AS**

Version: 1.0

Date of print 20.09.2018

1. Identification

Product identifier

VOGAEVA 200AS

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Product for construction chemicals Recommended use: for industrial and professional users







Details of the supplier of the safety data sheet

Company: VOGEL SYSTEMS Operating Division Construction Chemicals

E-mail address: info@vogel-systems.de

Emergency telephone number

International emergency number

VOGEL SYSTEMS Technical data sheet

Date / Revised: 19.09.2018 Product: **VOGAEVA 200AS** Version: 1.0

Date of print 20.09.2018

Curing surface hardner compound for fresh concrete

DESCRIPTION

VOGAEVA 200AS is an anti-evaporating liquid compound to prevent evaporation while mixing water in concrete.

APPLICATION FIELDS

VOGAEVA 200AS is useful in large areas of exposed concrete such as :

- · Parking areas
- Runways
- Highways
- · Roof-decks
- · Retaining walls.

APPLICATION TOOLS

Apply VOGAEVA 200AS BY motor operated spray gun or hand.

APPLICATION

- · Remove dirt, surface dust, laitance and any surface contamination e.g.
- Apply VOGAEVA 200AS directly to fresh concrete by the available tool.

TECHNICAL DATA

Product propreties (At 20°C)	
form	Solvent base
Full dry	1 hour
colour	Available in amber
Density	0.8 ±0.03 kg/l
Diluents	thinner

VOGEL SYSTEMS Technical data sheet

Date / Revised: 19.09.2018 Version: 1.0

Product: VOGAEVA 200AS

Date of print 20.09.2018

CLEANING

Tools and equipment should be cleaned, immediately after use, with thinner .Once product cures, this can only be removed by mechanical means.

CONSUMPTION

Estimated consumption for VOGAEVA 200AS Is 0.2 - 0.5 kg/m²

PACKAGING

VOGAEVA 200AS is supplied in 20 kg pails.

SAFETYAND HEALTH

VOGAEVA 200AS is a low toxicity product but direct contact with skin and eyes must be avoided .

Use rubber gloves and safety goggles when handling, mixing and applying the product.

STORAGE

Twenty four months in its unopened original packaging. Store in a cool, dry and covered place, protected from moisture, frost and direct sunlight, with temperatures between 5 °C and 30 °C.