

VOGATRAFFIC-LINE

PAGE 1 / 3

VOGEL SYSTEMS Technical data sheet
Date / Revised: 19.09.2018
Product: **VOGATRAFFIC-LINE**

Version: 1.0

Date of print 20.09.2018

1. Identification

Product identifier

VOGATRAFFIC-LINE

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Product for construction chemicals
Recommended use: for industrial and professional users



Details of the supplier of the safety data sheet

Company:
VOGEL SYSTEMS
Operating Division Construction Chemicals

E-mail address: info@vogel-systems.de

Emergency telephone number

International emergency number

Paint for marking roads and traffic signs

DESCRIPTION

VOGATRAFFIC-LINE is a Special paints for marking roads and traffic signs.

GENERAL SPECIFICATIONS:

one component ready to apply paint, based on chlorinated rubber, pigments, and special filling materials, which have high resistance to weather conditions, chemicals ..etc

APPLICATION TOOLS

Apply VOGATRAFFIC-LINE by brush, roller or spray gun.

APPLICATION

1. The road surface to be painted should be cleaned well, dry and totally free from oils, grease or any other contaminations which may prevent the paint adhesion.
2. It is preferable to remove the old paint in case of repainting.
3. The next coat should be painted after 45 minutes from the first coat.

TECHNICAL DATA

Product properties	
Density (kg/liter)	2.0 ± 0.2
Solid Content	> 60%
Initial Drying Time	10 - 15 minutes
Hard Drying Time	45 - 60 minutes
Colors	White, Yellow and other colors
Abrasion Resistance	> 1400 cycles

CLEANING

Tools and equipment should be cleaned, immediately after use, with water. Once product cures, this can only be removed by mechanical means.

CONSUMPTION

Estimated consumption for **VOGATRAFFIC-LINE** is 0.2-0.25 kg/m/coat.

PACKAGING

VOGATRAFFIC-LINE is supplied in 4kg , 16 kg , 20 kg pack.

STORAGE

Twelve months in its unopened original packaging. Store in a cool, dry and covered place, protected from moisture , frost and direct sunlight, with temperatures between 5 °C and 30 °C.

SAFETY AND HEALTH

VOGATRAFFIC-LINE is a low toxicity product but direct contact with skin and eyes must be avoided .

Use rubber gloves and safety goggles when handling, mixing and applying the product.